

**NS-37852**

**Lewins Line**

**NS-37852 Modular Faceplate Double Cat**

**6, Two Port**



**Product Classification**

<b>Portfolio</b>	<b>LEWINS-LINE®</b>
<b>Product Type</b>	<b>Faceplate Double</b>
<b>Regional Availability</b>	<b>Asia   Australia/China  </b>



©2020 LEWINS-LINE, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of LEWIN-LINE. All specifications are subject to change without notice. See [www.Lewins-line.com](http://www.Lewins-line.com) for the most current information.

Revised: February 02, 2020

**Lewins Line****Technical Information**

<b>Faceplate Double Type</b>	<b>U/UTP Faceplate Double CAT 6</b>	
<b>Dimensions</b>	Depth	8.8mm   0.35 in
	Height	8.5mm   3.38 in
	Width	8.5mm   3.38 in
<b>General Specifications</b>	Cable Type	U / UTP (Unshielded)
	Color	White
	Package Quantity	1
	Total Ports	2 Port
<b>Mechanical Specifications</b>	Material Type	High-impact, flame retardant, thermoplastic ®

**Regulatory Compliance/Certifications**

**Agency**      Classification

**ISO 2017**      Designed, manufactured and/or distributed  
under this quality management system.



## Lewins Line

### **Feature/Regulatory Compliance/Certifications**

- ❖ Complies with TIA/EIA 568B.2-1 and ISO/IEC 11801 standards
- ❖ Through the continuous impedance analysis of the pin, terminals, and printed circuits, the best impedance matching relationship is achieved;
- ❖ Pin with gold plating to prevent surface oxidation, improve contact performance, and ensure performance and service life.
- ❖ Using high-quality flame-retardant polycarbonate material, flame retardant performance reaches UL94V-0 level.
- ❖ Supports mainstream termination methods to ensure universal connectivity and reliability of connections.
- ❖ Tool-less rotary threading, novel design, simple, beautiful, and compact.

