
NS-25619

Lewins Line

NS-25619 Modular Faceplate Single Cat

6, One Port



Product Classification

Portfolio **LEWINS-LINE®**

Product Type **Faceplate Single**

Regional Availability **Asia | Australia/China |**



©2020 LEWINS-LINE, Inc. All rights reserved. All trademarks identified by ® or ™ are registered trademarks, respectively, of LEWIN-LINE. All specifications are subject to change without notice. See www.Lewins-line.com for the most current information.

Revised: February 02, 2020

Lewins Line

Technical Information

<i>Faceplate Single Type</i>	<i>U/UTP Faceplate Single CAT 6</i>	
<i>Dimensions</i>	Depth	8.8mm 0.35 in
	Height	8.5mm 3.38 in
	Width	8.5mm 3.38 in
<i>General Specifications</i>	Cable Type	U / UTP (Unshielded)
	Color	White
	Package Quantity	1
	Total Ports	1 Port
<i>Mechanical Specifications</i>	Material Type	High-impact, flame retardant, thermoplastic ®

Regulatory Compliance/Certifications

Agency

Classification

ISO 2017

Designed, manufactured and/or distributed
under this quality management system.



Lewins Line

Feature/Regulatory Compliance/Certifications

- ❖ Complies with TIA/EIA 568B.2-1 and ISO/IEC 11801 standards
- ❖ Through the continuous impedance analysis of the pin, terminals, and printed circuits, the best impedance matching relationship is achieved;
- ❖ Pin with gold plating to prevent surface oxidation, improve contact performance, and ensure performance and service life.
- ❖ Using high-quality flame-retardant polycarbonate material, flame retardant performance reaches UL94V-0 level.
- ❖ Supports mainstream termination methods to ensure universal connectivity and reliability of connections.
- ❖ Tool-less rotary threading, novel design, simple, beautiful, and compact.

